

What is claimed is:

1 (currently amended). A shower support comprising ~~for~~
 2 a shower head and a hose, ~~comprising~~
 3 a mounting fixture for mounting the support such that the support is
 4 adjustable,
 5 ~~on~~ a pivotable arm jutting out of the mounting fixture, said arm having
 6 a first end connected to the mounting fixture and a second opposite end,
 7 with a water conduit extending from the mounting fixture to at least one
 8 additional shower fixture attached along said arm,
 9 a receptacle adapted to receive ~~for a~~ the shower head when the
 10 shower head is not in hand operation, said receptacle being arranged ~~in~~
 11 ~~the vicinity of a far~~ at said second opposite end of the arm away from the
 12 mounting fixture, ~~which~~ wherein the shower head and the receptacle ~~is~~ are
 13 configured ~~such that the~~ to allow the shower head ~~is detachable~~ to be
 14 removed from the receptacle during hand operation of the shower head
 15 on the hose ~~from said receptacle~~, and
 16 ~~at least one additional shower fixture attached to the arm,~~
 17 wherein the shower head is supplied with water by the ~~a~~ hose and
 18 wherein the additional shower fixture is arranged to be supplied with water by
 19 the water conduit independently of the shower head.

Claim 2 is canceled.

1 3(currently amended). The shower support according to claim 1,
 2 wherein the water conduit is defined by a channel that extends through the
 3 arm and leads to the additional shower fixture.

1 4(previously presented). The shower support according to claim 1,
 2 wherein the arm comprises a length of hollow, profiled stock, at least from the
 3 mounting fixture to the additional shower fixture.

1 5(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is arranged between the mounting fixture
3 and the far end of the arm.

1 6(previously presented). The shower support according to claim 1,
2 wherein a direction of a jet exiting the additional shower fixture is adjustable.

1 7(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is mounted on a side of the arm jutting
3 from the mounting fixture.

1 8(previously presented). The shower support according to claim 1,
2 wherein at least one said additional shower fixture is mounted on a underside
3 of the arm jutting from the mounting fixture.

1 9(currently amended). The shower support according to claim 1,
2 having ~~several~~ **multiple said** additional ~~said~~ shower fixtures and ~~a water~~
3 **wherein the water conduit provides a water** supply ~~conduit~~ common to all
4 the additional shower fixtures.

1 10(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is nondetachable.

Claim 11 was canceled.

1 12(previously presented). The shower support according to claim 1,
2 wherein the arm is pivotable relative to the mounting fixture about a horizontal
3 axis orthogonal to a longitudinal axis of the arm.

4 13(previously presented). The shower support according to claim 12,
5 wherein a water conduit passes a pivotable connection of the arm to the
6 mounting fixture.

1 14(previously presented). The shower support according to claim 1,
2 wherein the arm is configured in the form of a fork.

1 15(previously presented). The shower support according to claim 14,
2 wherein the additional shower fixtures are arranged on outer faces of tines of
3 the fork.

Claims 16 and 17 were canceled.